

Botron B17000/5 Technical Data Sheet



Overview:

Botron's Conductive Tubing is made of a volume conductive material designed for specialized storage or packaging. Our conductive bags do not contaminate components they come in contact with, despite repeated use. The B17000/5 Conductive Tubing is heat-sealable, non-abrading and can be easily grounded.

Product Notes and Features

- Heat Sealable
- Non-Abrading
- Easily Grounded

PROPERTIES

SPECIFICATIONS

Color:	Black
Size:	5" x 500'
Surface Resistivity:	<1,000 ohms/sq.
Volume Resistivity:	<300 ohms/cm
Elongation (MD%):	>150%
Tensile Strength:	>2,000 psi
Tear Strength:	>400 lbs. per inch
Burst:	20 to 60 psi
Temperature:	250° to 375°
Time:	0.5 to 3.5 seconds
Pressure:	30 to 70 psi



PART NUMBERS

- B17000/5** 5" x 500' 4mil
- B17000/8** 8" x 500' 4mil
- B17000/10** 10" x 500' 4mil
- B17000/12** 12" x 500' 4mil

Botron Company Inc. | 21601 N 21st Ave Phoenix AZ 85027 | Ph# 623-582-6700 | Fax# 623-582-6776

Disclaimer. All statements of technical information are believed to be true and are based upon tests we believe to be reliable. The proper use and application for this product must be the responsibility of the user.

The statements herein shall have no force or effect.